

olivetti



EXPLOR@VX N and VX E

INTEGRATED POS TOUCH SCREEN

Explor@VX N and **VX E** are the multi-functional touch screen POS specifically addressed to the hospitality use.

Enhanced operating flexibility thanks to the tiltable display, USB & cash drawer control and a **small footprint** concept.

In its fanless version, **Explor@VX N** is also **extremely silent**, while the enhanced versions **Explor@VX E** are **high performance**.

With its compact, stylish and vertical design, **Explor@VX N** and **VX E** are suitable for any environment and use.

MULTI-FUNCTIONAL TOUCH SCREEN POS

SMALL FOOTPRINT

ADJUSTABLE VIEW ANGLE DISPLAY FOR DIFFERENT ENVIRONMENTS

EASY ACCESS TO KEY COMPONENTS

IDEAL FOR HOSPITALITY THANKS TO PROTECTION AGAINST DUST AND WATER (IP54)



TOOL FREE ACCESS TO HARD DISK



MAGNETIC CARD READER, SMART IC CARD READER (optional)



CUSTOMER DISPLAY OR LCD SECOND DISPLAY (optionals)

TECHNICAL SPECIFICATIONS

MOTHERBOARD	CPU Support	Explor@VX N (Fanless): Intel Atom N270 1.6GHz Explor@VX E (Fan): Intel Celeron M 1.86GHz/ Pentium Core 2 Duo 1.66GHz	System Memory	Explor@VX N (Fanless): SO-DIMM DDR2 2 sockets, up to 2GB Explor@VX E (Fan): SO-DIMM DDR2 2 sockets, up to 4GB
	Chipset	Explor@VX N (Fanless): Intel 945GSE + ICH7M FSB533MHz Explor@VX E (Fan): Intel 945GME + ICH7M FSB 400/533/667MHz	Graphic Memory	Explor@VX N (Fanless)/VX E (Fan): Shared system memory up to 224MB
	MB	Explor@VX N (Fanless): B68 Explor@VX E (Fan): B98	Expansion	Explor@VX N (Fanless): Mini PCI-E slot Explor@VX E (Fan): Mini PCI slot
LCD/TOUCH PANEL	LCD Size	15" TFT LCD	Touch Screen Type	ELO Resistive (5 wires)
	Brightness (nits)	250	Tilt Angle	0° ~ 80°
Resolution	Max 1024 x 768			
STORAGE	HDD	3,5" SATA HDD (min 160 GB)	Flash Memory	By optional SSD (Instead of HDD)
	Control / Indicator	Power Button LED indicator	Rear I/O	Serial/COM: 4 x COM ports RJ-45: COM1 standard RS-232; COM2 RS-232/ RS-422/ RS485 (by jumper); COM3 & COM4 pin10 with 5V/12V (by jumper) USB: 4 ports (V2.0) Parallel Port: 1 LAN (10/100/1000): 1 x RJ45 Cash Drawer: 1 x RJ11 (12V/19V) 2nd VGA Output: 1 DC Jack: 1 Audio: 1 x Line out, 1 x Mic-in
Front I/O	USB: 2 ports (V2.0)			
ENVIRONMENT	EMC & Safety	Class A, CE	Operating Temperature	5° C ~ 35° C
	Power Supply	Power adapter external 19V/90W	Storage Temperature	-20° C ~ 55° C
OPTIONS	MSR	MSR 3 tracks (PS2)	3 in 1 MSR	MSR 3 tracks (PS2)+i-Button reader+ Smart IC Card Reader (USB)
	2 in 1 MSR	MSR 3 tracks (PS2)+Smart IC Card Reader (USB) MSR 3 tracks (PS2)+Finger print reader (USB) MSR 3 tracks (PS2)+i-Button reader (PS2)	Customer Display	VFD 2 x 20 characters (COM)
			Second Display	10.4" LCD without touch
Audio	Built in Speaker 2 x 2W speakers (optional)			
VARIOUS	Operating Systems	WEPOS, POSReady 2009, Windows XP, XP Embedded, Windows 7, Linux	Dimensions (WxDxH) and weight	355 x 145 x 363 mm (with LCD 90°) 9 kgs

Product performances are referred to an appropriate use under optimal conditions. With the right to change technical specifications. The registered trademarks are the property of their respective owners.

EXPLOR@VX N and VX E are distributed by Olivetti S.p.A.

(05/11) - Code: 700052-00

OLIVETTI S.P.A.
VIA JERVIS 77
10015 IVREA (TO) ITALY
www.olivetti.com